



CLEAN COPY

[0007] The interlabial pad, fixed by inserting it between the labia, has characteristics that it is difficult to cause the leak of menstrual blood because of higher adhesion to the body than that of the sanitary napkin and psychological resistance thereof on wearing is lower than that of the tampon which is inserted into the vagina.

[0008] However, interlabial pads have a drawback that it is more difficult to wear them than sanitary napkins because interlabial pads are wrapped in the interlabial space whose visual check is difficult. Further, if an interlabial pad is not worn to an appropriate point, menstrual blood leakage results in immense damage because the interlabial pad is smaller than the sanitary napkin. Furthermore, the interlabial pad is more likely to be mis-worn than the tampon.

[0009] With regard to the present inventions for dissolving wearing troubles in interlabial pads, pct international publication no. Wo99/56689 discloses a pad having a structure that a projection is formed on the opposite side to the body-contacting surface. With this structure, a wearer can wear a pad by taking the projection with fingers. It is supposed that that this kind of pad can be worn more readily than a pad without a projection. (refer to FIG. 31)

[0010] It is required to take the projection of a pad with at least two fingers such as a thumb, a forefinger or others for wearing such a interlabial pad. So, balls of fingers (fingerprint sides) having a fineness of perception are used to take the projection and positioned on the side face of the projection. More specifically, the wearer should detect the wearing point with the tips of her nails when fixing an interlabial pad. So, actually, a wearer should trust her intuition and it is rather difficult for her to detect an appropriate wearing point. Especially, females often let their nails grow long or wear artificial nails. So, in some cases, it is almost impossible to fix conventional interlabial pads provided above to an appropriate point.

[0011] As just described, easy wearing through correct detection of a wearing point, reduction of mis-wearing and sufficient adhesion onto the pubic region have not been

## CLEAN COPY

realized by the conventional interlabial pads provided above. Further, there are still cases where menstrual blood adheres to fingertips when fixing a pad, causing psychological oppositions to use an interlabial pad.

[0012] Furthermore, conventional interlabial pads provided above are likely to be misaligned to the interlabial space because the position of fingers to take pads is not stable, resulting in a risk of mis-wearing.

## SUMMARY OF THE INVENTION

[0013] The present invention has been made to solve the problems provided above. An object of the present invention is to provide an interlabial pad with a structure that is capable of wearing the pad securely and sanitarily to the interlabial space of females.

[0014] The above objects can be attained, according to the present invention, by an interlabial pad comprising: a structure that an interlabial pad is fixed in such a way that it contacts the pubic region by using dexterously a ball of a finger having a fineness of perception to check the fixing point, more specifically, a structure that a finger insertion opening into which a finger can be inserted contacting a side of an interlabial pad opposite to the body and a finger insertion opening connected thereto are provided, and a stopper to prevent further insertion of a finger is provided in the finger insertion opening at a position capable of fixing an interlabial pad effectively, in order to wear an interlabial pad to the interlabial space with a positional relationship of a finger to an interlabial pad being stable and smoothly fix an interlabial pad to the interlabial space.

[0015] More specifically, the present invention provides the following features:

[0016] An interlabial pad capable of absorbent body fluid formed into a substantial rectangle having a longitudinal direction and a lateral direction provided with a size, weight and flexibility allowing to be pinched and held in between the labia without forcing, comprising a body side face orientated to the body side and an opposite side face

[0017] wherein the interlabial pad has a finger insertion cavity, formed along the longitudinal direction on the opposite side face to body, for inserting a finger of the wearer, and an opening portion of the finger insertion cavity constitutes a finger insertion opening for directly securing an opening in the fingerbreadth direction in the planar direction of the opposite side face to body;

[0019] a finger insertion restriction portion for restricting the advance of the insertion of the finger from the finger insertion opening in the finger insertion cavity, is provided in the vicinity of the finger application point.

[0021] The finger insertion restriction portion is provided at a place of the interlabial pad so that a ball of finger inserted into the finger insertion cavity stays there and pushes open

## CLEAN COPY

a pair of the labia through the interlabial pad to detect the ostium vaginae that is situated in the back of the interlabial space. So, any wearer can detect the ostium vaginae easily. Therefore, the interlabial pad can be fixed to an appropriate position inside of the labia that is hardly visible.

[0022] In this specification, "finger breadth directions" denotes a direction other than the direction of finger thickness, specifically, it denotes the direction of nail width. "opening of finger breadth" denotes an opening having an enough size to insert a finger.

[0023] Also in this specification, "directed" denotes that something is aligned to a specified direction.

[0024] In this specification, a "front end" of the interlabial pad denotes an end that is located at the clitoral side (referred to as the "front side" hereafter) when the pad is fixed. A "rear end" of the interlabial pad denotes an end that is located at the analis side (referred to as the "rear side" hereafter) when the pad is fixed.

[0025] An implementation of the interlabial pad includes a mini sheet piece disposed in a way to stride from one side to the other side taking the longitudinal direction of the interlabial pad as a central axis, on the opposite side face to body of the interlabial pad, wherein: the finger insertion opening is formed between the mini sheet piece and the opposite side face to body.

[0026] According to an implementation the invention, a mini sheet piece is attached to the side of an interlabial pad opposite to body. With a simple configuration that the mini sheet piece is provided, a finger insertion cavity is formed to make fixing of the interlabial pad easier-by wearing the interlabial pad on a tip of a finger.

[0027] In the interlabial pad with such a mini sheet piece, the mini sheet piece is preferably provided at a position from the middle to the rear end of the interlabial pad in the longitudinal direction. By this, a ball of a finger in the top joint is made to contact the

[0028] According to an implementation of the interlabial pad, the finger insertion restriction portion is formed as a portion where a part of the finger insertion cavity is made narrow.

[0030] According to another implementation of the interlabial pad, the finger insertion restriction portion is formed by binding the opposite side face to body each other.

[0031] According to an implementation, the finger insertion restriction portion is formed by bonding areas on the opposite side to the body side and those are facing each other when the interlabial pad is folded. So, a long convex area that is convexly curved towards the body face side is formed in the longitudinal direction at the body face side near the finger insertion restriction portion.

[0033] In an area corresponding to the finger insertion restriction portion, even if a finger is inserted into the finger insertion opening, the state of narrowed width at the top of the long convex area where the interlabial pad is folded and maintained as it is. So, the top portion can be a starting point to insert the long convex area into a position near the ostium vaginae. A wearer can tightly fit the top of the long convex area into the ostium vaginae that is situated in the penetralia of the interlabial space (vestibule) using a ball of a finger in the top joint inserted in the finger insertion opening through the interlabial pad.

[0035] In addition, since the long convex area is formed by folding the interlabial pad, it is deformed according to the shape of a finger inserted into the finger insertion opening formed inside of a part of the longer convex area when fixing the interlabial pad. However, when a finger is pulled out, it can be transformed according to the shape between the labia. As the result, the body face side of the interlabial pad can be tightly fixed to inside of the labia when fixing an interlabial pad in spite of the shape differences of the labia of wearers.

[0037] According to an implementation, the finger insertion opening is formed in such a way that it gets smaller gradually from the finger insertion opening (largest) to the finger

## CLEAN COPY

insertion restriction portion (smallest). Consequently, a finger inserted along inside of the opposite side to the body side from the finger insertion opening to the finger insertion opening is guided gradually and smoothly into the finger insertion restriction portion. As the result, accidents such as a break of a sheet provided at the opposite side of body by movement of a finger inserted into the finger insertion opening or a poor bonding between the opposite side to the body side and the mini sheet piece can be prevented.

[0038] According to an implementation of the interlabial pad , a interval dimension of the finger insertion opening and the finger insertion restriction portion is 10% to 80% of the length dimension in the longitudinal direction of the opposite side face to body.

[0039] According to the implementation , the finger insertion opening is provided at the position 20% to 50% from the front end of an interlabial pad. The finger insertion restriction portion is positioned 60% to 100% from the front end of the interlabial pad. So, the interval between the finger insertion opening and the finger insertion restriction portion in the longitudinal direction falls under the range from 10 to 80% of the longitudinal dimension of the interlabial pad.

[0040] As described above, since the interval from the finger insertion opening to the finger insertion restriction portion is 10% or more to the longitudinal dimension of the interlabial pad, a finger inserted into the finger insertion opening is not likely to come out from the finger insertion opening resulting in reliable retention of a finger against the interlabial pad. Consequently, displacement of a finger in the finger insertion opening is prevented resulting in avoiding positional displacement against the labia when fixing the interlabial pad.

[0041] Since the interval dimension from the finger insertion opening to the finger insertion restriction portion is 80% or less of the longitudinal dimension of the interlabial pad, the mini sheet piece does not prevent a finger from pulling out from the finger insertion opening after fixing the interlabial pad. So, a finger can be pulled out smoothly, and positional displacement of the interlabial pad caused by the contact between the



[0042] According to an implementation of the interlabial pad, the finger insertion restriction portion is formed to position near one end edge in the longitudinal direction of the opposite side face to body.

[0044] According to an implementation of the interlabial pad, a fingertip exit for protruding the nail tip of the inserted finger is formed, in the finger insertion restriction portion.

[0046] According to an implementation of the interlabial pad, the finger insertion restriction portion is formed at a position biased to the center thereof by a predetermined dimension in the longitudinal direction from one end edge in the longitudinal direction of the opposite side face to body.

{W:\20050\0200479US0\00573815.DOC 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27 28 29 30 31 32 33 34 35 36 37 38 39 40 41 42 43 44 45 46 47 48 49 50 }

CLEAN COPY

the rear end of the interlabial pad. So, the interlabial pad covers a fingertip like a hood (refer to FIG. 8) and makes a wearer detect the position of the ostium vaginae using whole surface of a finger ball in the top joint including the fingertip. Consequently, a wearer can detect the ostium vaginae easily and fix the interlabial pad to an appropriate position more securely.

[0048] Also, adhesion of menstrual blood not only to a finger inserted into the finger insertion opening but also a nail sticking out from the nail tip escapement can be prevented since the interlabial pad covers a nail protruding from the nail tip escapement.

[0049] According to an implementation of the interlabial pad, a finger insertion compulsory portion is formed for tilting compulsorily the finger insertion direction to the opposite side face to body toward the finger insertion restriction portion in the finger insertion cavity.

[0050] According to another implementation, insertion direction of a finger is forced to slant in the direction of opposite side to the-body side due to the finger insertion direction forcing portion in the process of inserting a finger from the finger insertion opening into the finger insertion opening when fixing an interlabial pad. Consequently, a ball of a finger in the top joint can be fit to the opposite side to the body side more securely at the point when the fingertip reached the finger insertion restriction portion and the position of the ostium vaginae can be detected by a ball of a finger through each sheet and absorbent body more securely.

[0051] According to another implementation, the finger insertion compulsory portion is formed by the shape of folding of the mini sheet piece into the finger insertion cavity.

[0052] A part of the mini sheet piece is folded in the finger insertion opening in such a way that the interval between the mini sheet and the back side sheet decreases gradually. So, a finger is inserted in such a way that the outside of a finger (nail side) touches the mini sheet piece whose distance dimension against the opposite side of body decreases

gradually starting from the finger insertion opening in the process of inserting a finger from the finger insertion opening into the finger insertion opening when fixing the interlabial pad. Consequently, a fingertip (tip of a nail) can be guided to the finger insertion restriction portion more smoothly. As the result, accidents such as a break of the opposite side to the body side by movement of a finger inserted into the finger insertion opening or poor bonding between the opposite side to the body side and the mini sheet piece can be prevented.

[0054] According to still another implementation of the invention, the interlabial pad and a sanitary napkin can be used at the same time. Some women use several napkins layered when an amount of menstrual blood is large. However, there were problems such as bulky feeling, outer appearance change. In addition, sanitary napkins are layered on areas other than a vicinity of the ostium vaginae where layered pads are not required resulting rash, excessive humidity. In this respect, with the interlabial pad according to the present invention, sanitary products are layered only on the labia and their vicinity having little effect on wear feeling and outer appearance, and in addition, occurrence of excessive humidity and rash around hips can be reduced. Further, it becomes possible that only the interlabial pads according to the present invention are changed without replacing sanitary napkins. A wearer does not have to carry auxiliary sanitary napkins that have a conspicuous size. Sanitary napkins here may include not only napkins sold as products for absorbing menstrual blood but also vaginal discharge absorbing sheets.

[0056] The pad can be used for incontinence absorb pad. That is ostium vaginae where the menstrual blood is discharged and a urethral meatus where urine is discharged locate between labia, and the interlabial pad of the present invention to be used between labia can absorb urine also.

CLEAN COPY

[0057] As described hereinbefore, the pad of the invention can absorb urine around labia, especially around the urethral meatus and is useful for the absorbing pad for incontinence, especially for a light incontinence.

[0058] The interlabial pad can be a pad for absorbing vaginal discharge.

[0059] Furthermore, the interlabial pad can be used as a pad for absorbing the vaginal discharge. The interlabial pad is used between labia and can absorb the excretion other than the menstrual blood from ostium vaginae for the use therefore (for absorbing the vaginal discharge).

[0060] As described above, the pad can absorb the vaginal discharge in order to decrease the discomfort for the person, and is useful for the user who is not menstruating.

[0061] With regard to a wrapping body including the interlabial pad and a wrapping container containing this interlabial pad, the interlabial pad is contained by folding so that the finger insertion opening opens when the wrapping container is unwrapped.

[0062] According to an implementation of the present invention , since the interlabial pad is contained in a wrapping container in such a way that the finger insertion opening is opened when the wrapping container is unsealed, a wearer can insert a finger into the finger insertion opening quickly and smoothly. Consequently, operation to fix the interlabial pad fixing becomes easier.

[0063] With regard to a wrapping body the wrapping container is provided with a mark indicating the unwrapping direction identical to the insertion direction of the finger into the finger insertion opening.

[0064] According to an implementation of the prevention , a wearer can know the unsealing direction to expose the finger insertion opening without opening the wrapping

container. Consequently, it prevents a wearer from mistaking an unsealing direction. It also makes the direction to unseal the wrapping container and the direction to insert a finger into the finger insertion opening always aligned.

[0066] (17) With regard to an wrapping body the mini sheet piece in the interlabial pad is folded outward in a shape swelling toward the body side.

### BRIEF DESCRIPTION OF THE DRAWINGS



[0079] FIG. 12 is a schematic cross section diagram to explain the cross sectional structure of the finger insertion restriction portion according to the example of the present invention, showing the state that the sides opposite to body of the back side sheet are bonded with an adhesive in such a way that a space of the long convex area is crossed;

[0081] FIG. 14 (a) shows the state that a finger is inserted into the interlabial pad wherein the mini sheet piece is formed to reach the end edge of the side opposite to body of the back side sheet, and the finger insertion restriction portion is formed being positioned near one end edge in the longitudinal direction of the side opposite to body, FIG. 14(b) shows the state that a finger is inserted into the interlabial pad wherein the mini sheet piece is formed to reach a position distant by a specified dimension from the end edge of the opposite side to the body side of the back side sheet, and the finger insertion restriction portion is formed at a position to the center by a specified dimension in the longitudinal direction on the opposite side to the body side, and FIG. 14(c) is a schematic diagram to explain the state that a finger is to be inserted into the interlabial pad wherein the mini sheet pieces are separated and provided in parallel to the longitudinal direction of the opposite side to the body side;

[0083] FIG. 16 is a schematic side view showing the state of a finger with dotted lines inserted into the finger insertion opening using the interlabial pad where a nail tip escapement is formed at the finger insertion restriction portion;

CLEAN COPY

escapement from which a nail tip protrudes is formed at the finger insertion restriction portion;

[0085] FIG. 18 is a schematic diagram to explain the length of total inside perimeter of the finger insertion opening of the interlabial pad according to the example of the present invention;

[0086] FIG. 19 is a schematic diagram to explain the linear dimension in the lateral direction of the interlabial pad;

[0087] FIG. 20 is a schematic perspective view showing a transformational example of the interlabial pad according to the the present example and the structure where the finger insertion direction restriction portion is formed with the shape of the mini sheet piece folded into the finger insertion opening;

[0088] FIG. 21 is a schematic diagram showing an example of the transformed interlabial pad according to the example of the present invention and the state that the inserting direction of a finger is forced to slant towards the opposite side to the body side facing the finger insertion restriction portion;

[0089] FIG. 22 is a cross section diagram of a cross section VI-VI of the interlabial pad in FIG. 21 showing the state of a finger in the finger insertion opening;

[0090] FIG. 23 is a cross section diagram of a cross section V-V of the interlabial pad in FIG. 21 showing the state of a finger in the finger insertion opening;

[0091] FIG. 24 is a cross section diagram of a cross section IV-IV of the interlabial pad in FIG. 21 showing the finger insertion restriction portion;

[0092] FIG. 25 is a schematic view to explain a method to measure the peel strength of adhesives for evaluating the adhesive force thereof;



CLEAN COPY

[0093] FIG. 26 is a diagram to explain a method to measure the shearing strength of adhesives in a valuation method of the adhesive strength of the adhesive formed on the body side surface of the surface side sheet;

[0094] FIG. 27 is a schematic perspective view showing a wrapping body where the interlabial pad indicated with broken lines is folded to be contained in such a way that the finger insertion opening will open when unsealing the wrapping container;

[0095] FIG. 28 is a schematic perspective view showing the state that a wrapping container marked with a sign indicating an unsealing direction aligned to the inserting direction of a finger inserted into the finger insertion opening of the interlabial pad contained therein is unsealed;

[0096] FIG. 29 is a schematic perspective view showing the state that a wrapping body where the mini sheet piece of the interlabial pad indicated with broken lines is folded facing outward in the shape plumping towards body is unsealed;

[0097] FIG. 30 is a schematic perspective view showing a wrapping body that is unsealed like opening a set of folded doors until the interlabial pad contained in a wrapping container is exposed;

[0098] FIG. 31 is a diagram showing the use condition of a conventional example with a projection on the reverse side of the interlabial pad.

## DETAILED DESCRIPTION OF THE INVENTION

[0099] An example of the present invention will now be explained referring to drawings. The present invention is not limited to the embodiment.

[0100] [Overall structure of the interlabial pad]



[0106] As described above, the finger insertion opening 6 is formed in such a way that the width dimension along the lateral direction decreases gradually towards the finger insertion restriction portion 8 starting from the finger insertion opening 7. So, a fingertip in the lateral direction of the side opposite to body is guided to the finger insertion restriction portion 8 gradually and smoothly only by inserting a finger from the finger insertion opening 7 to the finger insertion opening 6 along the inside of the side opposite to body. Consequently, breaks, etc of the sheet provided on the side opposite to body due to the finger insertion action into the finger insertion opening 6 can be prevented.

[0108] Wearing condition of the interlabial pad according to the example will now be explained. FIG. 5 is a schematic plane view showing the state that a finger is inserted into the finger insertion opening 6 of the interlabial pad according to the example. FIG. 6 is a schematic side view of the state that a finger is inserted into the finger insertion opening 6 of the interlabial pad according to the example. FIG. 7 is a schematic diagram to explain the state that the interlabial pad according to the example is fixed to the labia 18. FIG. 8 is a schematic diagram to explain the state that the ostium vaginae 18a is detected by a finger inserted in the finger insertion opening 6 of the interlabial pad according to the example. FIG. 9 is a schematic diagram to explain the state that the ostium vaginae 18a is detected by a finger inserted in the finger insertion opening of an interlabial pad without the finger insertion restriction portion.



according to the example will now be explained.

[0115] As shown above, the finger insertion restriction portion 8 is provided in the finger insertion opening 6 on the side opposite to body of the interlabial pad according to the example. The finger insertion restriction portion 8 is formed in the chevron space of the finger insertion opening 6 shown above by bonding the opposite sides to body of the back side sheet 4 to each other in the lateral direction of the interlabial pad. It stops the progress of finger insertion into the finger insertion opening 6 by narrowing the area of the space.

CLEAN COPY

opening 6 is preferably a "non through space".

[0117] Structure of the finger insertion restriction portion 8 is formed, specifically, for example, in a part of area where sides opposite to body of the back side sheet 4 contact to each other as shown in FIG. 10 or in almost whole area where sides opposite to body of the back side sheet 4 contact to each other as shown in FIG. 11 of the marginal area (the rear end area of the interlabial pad forming a bonding area between the surface side sheet 3 and the back side sheet 4 where no absorbent body exists) situated at the rear end of the long convex area 2 of the interlabial pad, by bonding the surface side sheet 3 and the back side sheet 4 by any one of or combination of heat embossing processing, hot melt type adhesives, etc.

[0118] It is also possible to apply hot melt type adhesives in dot pattern to the overlapped area of the sides opposite to body of the back side sheet 4. Further, as shown in FIG. 12, it is also possible to apply hot melt type adhesives in a stripe pattern in the middle of the long convex area 2 (the area where the absorbent body 5 exists) in such a way that the space in the long convex area 2 is crossed. By this structure, the wear feeling is not deteriorated due to the hardening around the bonded area.

[0119] The peel strength of the bonded area of the finger insertion restriction portion 8 is preferably 100 mn/25 mm or more. A risk that a finger inserted into the finger insertion opening 6 peels and protrudes from the finger insertion restriction portion 8 can be evaded by this peel strength.

[0120] A preferable example is that the finger insertion opening 7 is provided at the position of 40% from the front end of the interlabial pad, the finger insertion restriction portion 8 is provided at the position of 90% from the front end of the interlabial pad, a hot melt type adhesive is applied in a stripe pattern with 3 mm width on the garment-facing side of the reversal side sheet 4 in such a way the long convex area is at least crossed. The dimension of the mini sheet 1 in the longitudinal direction is preferably within the range of 40 to 100% from the front end of the interlabial pad.

[0122] Further, since the long convex area 2 is formed by just folding the main body of the interlabial pad, it can be transformed according to the shape of the finger when fixed. A wearer can detect without sense of discomfort the position of the ostium vaginae that is positioned at the penetralia part (vestibule) with a finger in the top joint inserted into the finger insertion opening 6 through the sheet 3, 4 and the absorbent body 5 shown above. After fixing, the interlabial pad is fit to the interlabial space tightly since the long convex area 2 can be transformed according to the interlabial space.

[0124] The mini sheet piece now will be explained. FIGS. 13A-D illustrate a schematic view to explain the bonding part between the mini sheet piece 1 and the side opposite to body of the back side sheet 4. FIG. 14 is a figure to explain the state that mini sheet pieces` 21 that are different from the mini sheet 1 in shape are attached to the side

CLEAN COPY

opposite to body of the interlabial pad.

[0125] [Length of the mini sheet piece]

[0126] Length of the mini sheet 1 is preferably 10% or more, more preferably 50% or more to the longitudinal dimension of the interlabial pad. With this length, a finger once inserted into the finger insertion opening 6 from the finger insertion opening 7 will not be pulled out, a finger will not move in the finger insertion opening 6 and the state that a ball of a finger is facing the back side sheet 4 of the finger insertion opening 6 can be maintained.

[0127] Further, the length of the mini sheet piece 1 is preferably 80% or less, more preferably 70% or less to the longitudinal direction of the interlabial pad. "linear dimension" of the mini sheet piece plays a role to denote "the positional relationship between the finger insertion opening 7 and the finger insertion restriction portion 8 in the longitudinal direction of the interlabial pad" and at the same time plays a role to "suggest the finger insertion direction". If the length is 80% or more to the longitudinal dimension of the interlabial pad, the mini sheet and the back side sheet are almost completely overlapped, and the function to "suggest the finger insertion direction" is not fulfilled sufficiently. As the result, a wearer may not be able to identify the finger insertion opening 7 and insert a finger therein. In this respect, by providing the mini sheet piece 1 having the dimension shown above, the problems can be evaded, and quick and smooth wearing of the interlabial pad on a fingertip is secured.

[0128] [Bonding position of the mini sheet piece in the lateral direction]

[0129] In the interlabial pad according to the present invention, the bonding area 9a between the surface side sheet 3 and the back side sheet 4 forms the side edge of the interlabial pad in the lateral direction. As shown in FIG. 13(a), if the bonding area 9b of the mini sheet piece 1 and the back side sheet 4 is positioned and fixed to this side edge area, the side edge of the interlabial pad becomes hardened, which may cause



CLEAN COPY

deterioration of wearing feeling.

[0130] This problem can be evaded by providing a bonding area other than the side edge shown above to fix the mini sheet piece 1. In this case, for example, as shown in FIG. 13(b), if the bonding area 9b between the mini sheet piece 1 and back side sheet 4 is positioned outside of the bonding area 9a, as shown FIG. 13(c), the bonding area 9b is likely to apart from the back side sheet 4 according to the action of a wearer, generating friction to skin to apply stimulus to a wearer. So, as shown in FIG. 13(d), the positions of bonding area 9a and 9b is preferably displaced, and the bonding area 9b is preferably provided in the position nearer to the center in the lateral direction of the interlabial pad than the bonding area 9a.

[0131] It is possible to use pressure-sensitive hot melts, thermo-sensitive hot melts, etc. For the adhesive to fix the mini sheet 1. It is possible to adopt sheet pattern, linear pattern, spiral pattern, dot pattern, etc for application of the adhesive. The mini sheet piece 1 may be cut in advance to conform to the fixing position shown above. The cutting process may be performed at the same time as other sheets with only the bonding position being different from other sheets. <non-bonding area of the mini sheet piece in the lateral direction of the interlabial pad>

[0132] The relationship between the shape of the mini sheet piece and the finger insertion restriction portion will now be explained. As shown in FIG. 14(a), if the mini sheet piece 21 forms the same shape as a part of the interlabial pad 20 and fixed in such a manner that it does not have non-bonding areas except the finger insertion opening 27, it is possible to provide the finger insertion restriction portion 28 at the rear end 20a of the interlabial pad 20. On the other hand, as shown in FIG. 14(b), if the mini sheet piece 21 is fixed in such a way that the second non-bonding area 27b exists in addition to the first non-bonding area 27a forming the finger insertion opening with the side opposite to the interlabial pad 20, the second non-bonding area 27b is provided in the rear of the finger inserting restriction portion 28. By this the mini sheet piece 21 is provided in such a way that outside of a fingertip (nail side) is covered and a fingertip (nail side) is guided to the

26

finger insertion restriction portion 28 securely resulting in reducing troubles that the ostium vaginae is not easily detected because a ball of a finger in the top joint is removed from the side opposite to body in the finger insertion opening 6. Further, since the bonding area between the interlabial pad 20 and the mini sheet piece 21 can be reduced, the area hardened by bonding them is reduced to improve wearing feeling.

[0133] Multiple mini sheet pieces may be fixed. In this case, as shown in FIG. 14 (c), the non-bonding areas of the mini sheet piece 21a and 21b in the lateral direction of the interlabial pad 20 is pluralized such as 27a, 27b, 27c, 27d. The finger insertion restriction portion 28 should be provided in front of the non-bonding area 27d at the backmost side of the interlabial pad 20, which is the end edge of the non-bonding area 27a and the finger inserting direction. By this, a fingertip can be guided into the finger insertion restriction portion 28 to prevent a ball of a finger in the top joint from removing from the finger insertion opening 26. In addition to that, since the mini sheet piece 21b is positioned wrapping a fingertip, exposure of the fingertip can be prevented. In addition to that, the area where a finger is covered by the mini sheet 21a and 21b can be reduced resulting in enlargement of flexibility in finger movement such as bend, stretch of a finger, enabling a finger to move more naturally in the operation that the interlabial pad 20 is pinched between the labia to further reduce positional displacement of the interlabial pad 20 against the labia. Multiple mini sheet pieces may be different in shape from one another. Mini sheet 21a and 21b may be different in shape to each other as shown in the example.

[0134] [nail tip escapement]

[0135] The nail tip escapement provided in the finger insertion opening will now be explained.

[0136] FIG. 15 is a schematic plan view showing in broken lines the state of a finger inserted into the finger insertion opening of the interlabial pad where a nail tip escapement is formed at the finger insertion restriction portion. FIG. 16 is a schematic

[0137] The interlabial pad according to the present invention, as shown in FIG. 15, nail tip escapement 11 can be provided at the finger insertion restriction portion 8 in such a way that a nail tip of a finger can protrude from the same.

[0139] In addition, since the finger insertion restriction portion 8 is formed at the position displaced from one end edge towards the center along the longitudinal direction on the opposite side to the body side, the back side sheet 4 exists for the nail tip protruded from the nail tip escapement 11 preventing adhesion of menstrual blood to the nail tip to improve sanitary conditions.

[0141] Dimension of the finger insertion opening will now be explained. FIG. 18 is a schematic view to explain the-total inside perimeter of the finger insertion opening 7 of the interlabial pad according to the example.

[0142] In FIG. 18, the sections not required for explaining the inside perimeter of the finger insertion opening 7 are denoted in dashed lines, wherein the inside perimeter of the finger insertion opening 7 is the distance shown by l.

CLEAN COPY

[0143] The total inside perimeter of the inside of the finger insertion opening 7 shown by "I" in FIG. 18 is preferably 30 to 120 mm and more preferably 40 to 80 mm. If the total inside perimeter length of the finger insertion opening 7 is smaller than 30 mm, the finger insertion opening 7 itself gets smaller to make insertion and pulling out of a finger difficult. If it is larger than 120 mm, it becomes hard to make a ball of a finger securely in touch with the back side sheet 4 in the finger insertion opening 6 resulting in poor retention of the interlabial pad by a finger to cause troubles in fixing the interlabial pad.

[0144] [Dimension of the interlabial pad]

[0145] The apparent dimension of the interlabial pad will now be explained. FIG. 19 is a figure to explain the linear dimension of the interlabial pad in the lateral direction.

[0146] The longitudinal direction of the interlabial pad is preferably 50 to 160 mm, more preferably 80 to 130 mm. With regard to this, if the linear dimension of the longitudinal direction is longer than 160 mm, the friction generated between the area that is not pinched by the interlabial space and shorts or sanitary napkins may exceed the pinching force by both labia resulting in removal of the interlabial pad. In the meantime, if the linear dimension in the longitudinal direction is less than 50 mm, since the area to be pinched by the labia becomes smaller, the contact area between the labia and the interlabial pad decreases to cause removal of the interlabial pad.

[0147] Apparent linear dimension of the interlabial pad in the lateral direction is preferably 10 to 60 mm, more preferably 20 to 40 mm. If the linear dimension in the lateral direction is longer than 60 mm, the area not pinched by the labia is rubbed by thighs of a wearer and the generated friction exceeds the pinching force by both labia resulting in removal of the interlabial pad. In the mean time, if the linear dimension of the lateral direction is shorter than 10 mm, since the area to be pinched between the labia becomes smaller, the contact area between the inside of the labia and the interlabial pad decreases to cause higher risk in removal of the interlabial pad.

[0148] "Apparent" used above denotes the distance between two points with the shortest linear dimension (falls under v in FIG. 19). This is a deliberate definition considering the case where the distance between two points in plan extended from a three dimensional shape is sometimes used as an actual distance (falls under w in FIG. 19) in relation to manufacturing process.

[0150] Other examples of the interlabial pad according to the present invention will now be explained.

[0152] In the interlabial pad 30 according to the example, as shown in FIG. 20, the finger insertion direction forcing portion 39 is formed to force the insertion direction of a finger in the finger insertion opening 36 to be slanted towards the opposite side of body of the back side sheet 34 facing the finger insertion restriction portion 38.

38.

[0155] [Construction materials of the interlabial pad]

[0157] Materials that are liquid hydrophilic and do not apply stimulus to skin are used for water permeable sheets provided at the body-facing side of the interlabial pad. They include nonwoven fabrics used alone or in combination manufactured by methods such as melt blown, spun bond, point bond, through air, needle punch, wet spun lace, foam film.

CLEAN COPY

[0159] Among these materials, considering liquid mobility from inside of the labia, chemical stimulation due to activators and the adhesiveness to inside of the labia, a spun lace nonwoven cloth wherein rayon of fineness 1.1 to 4.4 dtex and fiber length 7 to 51 mm is laminated by 40 to 80% of total specific weight per unit area on the body-facing side, rayon of fineness 1.1 to 4.4 dtex, fiber length 7 to 51 mm, 14 to 42% of total specific weight per unit area and pet of fineness 1.1 to 4.4 dtex, fiber length 7 to 51 mm, 6 to 18% of total specific weight per unit area are mixed to be laminated in such a way total specific weight per unit area of two layers is 20 to 60 g/m<sup>2</sup> on the garment-facing side, then, fibers are spun with one another by water flow spun lace and dried, the thickness thereof is adjusted in the range from 0.13 to 0.50 mm is preferable. In this case, bulkiness will be maintained even if the water permeable sheet is in wet condition by mixing pet on the garment-facing side to keep the adhesion to the inner wall of the labia.

[0160] <Absorbent body>

[0161] Materials to be used for the absorbent body contained in the interlabial pad include pulp, chemical pulp, rayon, acetate, natural cotton, water-absorbent polymer, fibrous water-absorbent polymer, synthetic fiber. They may be used alone or as a mixture of two or more. A mixture blended as required is made into a sheet by technologies such as pressure bonding by embossing, lacing by needling well known in the art. The sheets may be adjusted by bulkiness adjustment, layering, folding, etc as required.

[0162] Materials for a sheet may be used in a sheet shape or may be used by processing the same into powder. Their usages are not limited.

[0163] It is preferable for the absorbent body, although any material can be used as long as it is capable of absorbing and holding liquid (body fluid), to be bulky, hard-to-be deformed, less chemically stimulant, and highly flexible to fit into the labia. Specifically, a nonwoven sheet in which, 50 to 150 g/m<sup>2</sup> of pulp selected from the range of the fiber length of 1 to 10 mm is laminated on the garment face side and, on the body face side,

[0164] <Water impermeable sheet>

[0167] Further, when considering flexibility not spoiling wearing feeling, for example, a film selected from the range of specific weight per unit area from 15 to 30 g/m<sup>2</sup> composed mainly of low density polyethylene (ldpe) resin with density of 0.900 to 0.925 g/cm<sup>3</sup> is preferably used. More preferably, the film is emboss processed to reduce contact ratio and friction resistance by providing convex bossing in order to reduce a risk that the interlabial pad falls off from the labia due to a large friction caused by contact with other



[0168] <Mini sheet piece>

[0173] Nonwoven fabrics include: spun lace nonwoven fabrics made from complex synthetic fibers such as pe/pp, pe/pet, pp/pp having thermal shrinkage property, wherein core component has a high melting point and the sheath component has a lower melting point, and fibers are laced by water pressure; shrink type nonwoven fabrics wherein

## CLEAN COPY

shrinkage of fibers are accelerated by performing re-hot air processing; so called extensible spun bonds wherein continuous long fibers are applied with tentering after they are made into a sheet by heat seal.

[0174] More specifically, preferable materials rich in flexibility and drape feeling include shrink type nonwoven fabrics made from compound synthetic fiber such as pe/pp, pe/pet, pp/pp with fineness in the range from 1.1 to 4.4 dtex and the length in the range from 7 to 51 mm, having thermal shrinkage property, wherein the core component has a high melting point and sheath component has a lower melting point, a specific weight per unit area is adjusted in the range from 10 to 60 g/m<sup>2</sup>. Further, laminated types of the materials can be also used. Materials without extensibility applied with extensibility before use included: among nonwoven fabrics, through air nonwoven fabrics made from complex synthetic fibers such as pe/pp, pe/pet, pp/pp having thermal shrinkage property, wherein core component has a high melting point and the sheath component has a lower melting point; spun lace nonwoven fabrics wherein fibers are entangled by water pressure; spun bond nonwoven fabrics transformed into a sheet by layering continuous fibers; needle punch nonwoven fabrics wherein fibers are entangled to one another by needles; sms nonwoven fabrics wherein spun bond and melt-blown are layered in multiple layers to form a sheet; porous foam films; films mainly composed of pe resins. They may be used either alone or in combination of two or more.

[0175] Further, the materials can be applied with extensibility by corrugate processing wherein materials are fit between male and female dies and a shape is embossed by heat, temperature and pressure. More specifically, through air nonwoven fabrics composed mainly of complex synthetic fibers adjusted to the range of fineness 1.1 to 4.4 dtex and a specific weight per unit area of 10 to 60 g/m<sup>2</sup>, corrugated so that they can extend in the lateral direction are preferred. Corrugate processing is performed in such a way that male and female dies are provided so that extensibility is preferably obtained in the range of at least 10% and, more preferably, 20 to 50%, still further preferably, have a behavior in the range of 0.01 to 0.05n/25 mm of loads when 30% extended (test condition: tensilon tensile tester, speed, 100 mm/min, chuck interval, 100 mm). Other methods to apply

CLEAN COPY

extensity include cut lines, circular cutouts.

[0176] <adhesives>

[0177] Hot melt type adhesives generally used can be used for joining (bonding) materials. Examples include pressure sensitive hot melt adhesives and heat sensitive hot melt adhesives. Pressure sensitive hot melt adhesives are obtained by melting and mixing adhesiveness granting agents such as terpene resins, rosin resins and plasticizers such as waxes with synthetic rubber resins as main components including sis, sbs, styrene-ethylene-butadiene-styrene block copolymers (sebs), styrene-ethylene-propylene-styrene block copolymers (seps). Examples of heat sensitive hot melt adhesives include the ones composed mainly of olefin resins such as poly-a-olefin as a base resin. As shown above, there are many types of adhesives. Considering stability of application, however, it is desirable to use heat sensitive hot melt adhesives. Heat sensitive hot melt adhesives with higher application stability are those contain 45 to 55% of poly-a-olefin by weight, 10 to 15% of a plasticizer by weight and 35 to 45% of an adhesiveness granting agent by weight that are melt and blended. 0.1 to 1.0% of antioxidants, fluorescence inhibitors by weight may be added to this type of heat sensitive hot melt adhesives.

[0178] [Configuration of the interlabial pad applied with biodegradability, water dispersibility and water solubility]

[0179] The interlabial pad according to the present invention is preferably composed of biodegradable materials and/or water dispersible materials and/or water soluble materials. These kinds of interlabial pads can be fallen off into lavatory bowls as they are after use. So, pads can be disposed easily and cleanly. In addition, wastes in bathrooms can be reduced.

[0180] In this specification, "biodegradability" means that a substance is decomposed into gas such as carbon dioxide or methane, water, and biomass under anaerobic or aerobic condition according to the natural process under the existence of bacteria

## CLEAN COPY

represented by actinomycetes and other microbes, and also means that the biodegradability (biodegradable rate and biodegradable degree) of the substance equals to a material naturally generated such as fallen leaves or a synthetic polymer generally recognized having the same biodegradability under the same environment. "water dispersibility" has the same meaning as water degradability. It means a characteristic in which, while having no influence when used in a limited amount of moisture (menstrual blood), in a large amount of water or water current, the fabric is easily dispersed into small pieces at least to a degree where an ordinal toilet plumbing is not clogged. "water solubility" is a characteristic in which, while having no influence when used in a limited amount of moisture (menstrual blood), the fabric is soluble in a large amount of water or water current.

[0181] <Water permeable sheet >

[0182] Materials that can be used for water permeable sheets include: wet forming spun lace nonwoven fabrics with fiber length selected from 1 to 15 mm. Other materials include hydrolyzed biodegradable resins such as polylactic acid, polybutylene succinate. Examples include melt-blown nonwoven fabrics made from polylactic acid, whose specific weight per unit area is adjusted to the range of 20 to 60 g/m<sup>2</sup> and spun bond nonwoven fabrics whose specific weight per unit area is adjusted to the range of 15 to 30 g/m<sup>2</sup> and fineness is adjusted to the range of 1.1 to 3.3 dtex. Materials for nonwoven fabrics may or may not be holed.

[0183] For other materials, an acetate, a single synthetic fiber and a tow that is a continuous fiber composed of laminated bodies may be used by adjusting them to the range of specific weight per unit area from 50 to 300 g/m<sup>2</sup> and fibrillating their fibers.

[0184] <Absorbent body>

[0185] Nonwoven cloth sheets obtained by needling can be used for absorbent bodies. It is desirable to use carboxymethyl cellulose fibers considering biodegradability of super

## CLEAN COPY

absorbent polymer materials.

[0186] <Water impermeable sheet >

[0187] Materials usable for water impermeable sheets include: pva film; film sheets where one or both sides of, or partial surface of pva film is applied with water-repellent by applying silicone, etc; pva film mixed with silicone; starch films; films made from biodegradable resins of hydrolyzed polylactic acid; polybutylene succinates, etc and laminated papers with tissues, etc. If required, 0.1 to 5% of inorganic pigments may be mixed to color.

[0188] It is desirable to use laminated papers where films made from polylactic acid are laminated with tissues selected from the range of thickness of 10 to 20.mu. And specific weight per unit area of 15 to 20 g/m<sup>2</sup> and further composite area ratio when laminated is 5 to 40% considering maintenance of leakage resistance under hyper humidity and lower loads to septic tanks.

[0189] <Mini sheet piece>

[0190] Materials usable for the mini sheet piece include: films, spun bond nonwoven fabrics, melt-blown nonwoven fabrics, etc made from biodegradable materials such as polylactic acid; polybutylene succinate; films and nonwoven fabrics, etc made from soluble materials such as pva, cmc; water dispersible tissues, spun lace nonwoven fabrics, etc composed mainly of cellulose fibers, recycled cellulose fibers, etc.

[0191] Of these, spun bond nonwoven fabrics or melt-blown nonwoven fabrics composed mainly of biodegradable materials that are made into sheets whose fineness is adjusted to the range from 0.1 to 3.3 dtex, specific weight per unit area is adjusted to the range of 15 to 40 g/m<sup>2</sup>, obtained from the mechanical corrugate processing are preferred.

[0192] <Bonding methods>

[0194] It is possible to make a pad contact the interlabial space or external genitals by forming adhesion on a part of the body-facing side of the surface side sheet. It is also possible to prevent gaps from being generated between the pad and the body even when postures of a wearer are changed suddenly. So, a wearer can act freely without anxiety and restraining her activities.

[0196] Besides them, it is possible to use pressure sensitive hot melts to form adhesive areas. Pressure sensitive hot melts are obtained by melting and blending adhesiveness granting agents such as terpene resins, rosin resins; and plasticizers such as waxes with synthetic rubber resins such as sis, sbs, sebs, seps as a main component. Further, it is also possible to use silicone resin adhesives. Example of silicone resin adhesives include mixtures composed mainly of silicone resins and fluorocarbon resins, mixed with crosslinking agents such as platinum, molybdenum, antimony, and also mixed with plasticizers such as esters waxes, glycerin, machine oils.

{W:\2005\0200479US0\00573815.DOC {UNCLASSIFIED//FOR OFFICIAL USE ONLY} UNCLASSIFIED}

## CLEAN COPY

stability are the ones where 15 to 25% of sebs, 15 to 35% of a plasticizer by weight, 40 to 70% of an adhesiveness granting agent by weight are melted and blended. 0.1 to 1.0% of antioxidants, fluorescence inhibitors by weight may be added to this kind of pressure sensitive hot melt adhesives.

[0198] It is desirable to coat adhesive areas with a sheet of a tissue paper that is a separate paper generally available or a sheet of a film coated with a silicone resin. This can prevent adhesives from defeaturing and removing during storage.

[0199] Adhesives may be placed in plane, dot pattern, grid pattern, stripe pattern, etc. Application positions of adhesives are not particularly limited so far as they make fixing on body possible. It is particularly desirable to apply in stripe pattern of about 1 to 5 mm width near the both sides of the surface side sheet considering pubic hairs at the near side of the labia. An example of evaluating methods for the adhesive force will now be explained. These evaluation methods are to measure peel strength (refer to FIG. 25) and shear strength (refer to FIG. 26) of adhesives using a constant speed stretch tensile testing machine and stainless steel boards of 80 mm.times.50 mm (length.times.width). Before starting an evaluation test, an adhesive is applied by 25 mm.times.50 mm (width.times.length) on a polyethylene film that has almost same size as the stainless board. The film is let stand for 30 minutes under room temperature (20.degree. C.). Then, the polyethylene film is gently put on the stainless board so that the adhesive contact the board. A roller with weight of 2 kg is applied by just one-way. After that, test strips are made by letting it stand under room temperature (20.degree. C.) For 30 minutes. In the peel-strength test, the polyethylene film of the test strip is peeled by pulling it toward a direction indicated by an arrow a in FIG. 25. In the shear strength test, the film is pulled toward a direction indicated by an arrow b in FIG. 26. With regard to the test conditions, chuck interval (clamping interval) is 70 mm and pulling speed is 100 mm/min. In this test, the measured value of the peel strength is preferably 100 to 200 mn/25 mm, shear strength is preferably 2900 to 15000 mn/25 mm. These values are decided considering loads to skin of a wearer.

CLEAN COPY

[0200] [Wrapping body]

[0201] The wrapping body to wrap the interlabial pad according to the example in a wrapping container will now be explained. FIG. 27 is a schematic is perspective view showing a wrapping body 51 where the interlabial pad 10 indicated with broken lines is folded and contained in such a way that the finger insertion opening 7 will open when unsealing the wrapping container 50. FIG. 28 is a schematic perspective view showing the state that a wrapping body 61 is unsealed where the wrapping container 60 has a sign indicating an unsealing direction that is the same as the direction of a finger inserted into the finger insertion opening 7 of the interlabial pad 10 contained therein. FIG. 29 is a schematic perspective view showing the state that the wrapping body 71 is unsealed, where the mini sheet piece 7 of the interlabial pad 10 denoted by broken lines is folded right side out with the shape plumping towards the body-facing side. FIG. 30 is a schematic perspective view showing the state that the wrapping body 81 is unsealed, where the wrapping container 80 is opened like a set of folding doors until the interlabial pad contained in the wrapping container 80 is exposed.

[0202] The interlabial pad 10 according to the example of the present invention may be, as shown in FIG. 27, wrapping body 51 contained in the wrapping container 50. This kind of wrapping body 51 can be carried one by one since the interlabial pads 10 are wrapped independently. So, it is possible to handle them cleanly and conveniently compared to the case where multiple interlabial pads are contained in a single wrapping container.

[0203] In addition to that, in the wrapping body 51, the interlabial pad 10 is contained in the wrapping container 50 in such a way that the finger insertion opening 7 is opened toward the unsealing opening. "in such a way that the finger insertion opening 7 is opened toward the unsealing opening" shown above denotes, as shown in FIG. 27, the state that the interlabial pad 10 is contained in such a way that the mini sheet piece 1 and the finger insertion opening 7 formed by the same are exposed at the unsealing opening of the wrapping body 51 and a finger can be inserted into it immediately when the wrapping body 51 is opened. For example, the unsealing opening of the wrapping



## CLEAN COPY

container 50 in the wrapping body 51 is formed with perforations. It can be opened by pulling it from the backside to front side of the drawing. Then, the finger insertion opening 7 is exposed at the unsealing opening and opened towards the unsealing opening. So, a wearer can insert a finger into the finger insertion opening 7 immediately.

[0204] In this case, the wrapping body 51 is preferably constructed in such a way that it can be opened from only one direction, or as shown in FIG. 28, the wrapping container 60 is preferably marked with a sign 62 to indicate the opening direction. By these manners, the opening direction and the finger insertion opening 7 are aligned to the same direction and a wearer can insert a finger into the finger insertion opening 7 more quickly since the finger insertion opening 7 is always made to face a wearer.

[0205] Further, as shown in FIG. 29, the wrapping body 71 may be constructed in such a way that the mini sheet piece 1 is contained in the wrapping container 70 and mountain folded towards the opposite side of body along the substantial center line of the interlabial pad 10 in the longitudinal direction. By containing the interlabial pad 10 in the wrapping container 70, it is possible for a wearer to easily identify the position to which a finger is inserted and wear the interlabial pad 10 more speedily and easily since the finger insertion opening 7 that is folded opens by itself when opening the wrapping container 70. Opening methods of the wrapping container are not particularly limited. Methods usable include, as shown in FIG. 27 and 29, that a wrapping container is opened by cutting off the top edge, or as shown in FIG. 30, that the wrapping container 80 is opened by unsealing the top edge like opening a set of folding doors to take out the interlabial pad 10.

## [0206] INDUSTRIAL APPLICABILITY

[0207] As explained above, when a wearer wear the interlabial pad, a finger inserted into the finger insertion opening from the finger insertion opening, stays at the finger insertion restriction portion in the finger insertion opening. So, it becomes possible to stably hold the positional relationship between a ball of a finger in the top joint (fingerprint side) and

CLEAN COPY

the interlabial pad in the longitudinal direction, and to reduce the positional displacement against the labia when wearing the pad, further identify the fixing position of the interlabial pad more accurately by detecting the position of the ostium vaginae with a ball of a finger in the top joint having superior sensitivity.